

Barunah Pty Ltd

Incorporating:



Sherwell

Famson Ahrens



- > Field Bins
- > Silos & Silo Systems
- > Augers & Shifters
- > Feeders
- > Bulk Storage Systems



Sherwell Low Level Grain Silos

47 Tonne to 65 tonne capacity

Standard features include:

- Fully welded 30° or 45° base cone angle
- Zincalume steel construction in the tank
- Sight glasses and ground operated lid opener
- Easily accessible cone base manhole
- External ladder to centre fill optional
- Sherwell section ring beam eliminating grain traps

Grain Silos										
Model	M³	Approx. Tonnes	Cone	Diameter		Overall Height		Min. Auger Length		Retail* Exc. GST
				Ft	M	Ft	M	Ft	M	
1700	60	47	30°	14'	4.27	19'3"	5.87	36'	11	on request
2100	72	56	30°	14'	4.27	22'1"	6.73	39'	12	on request
2400	83	65	30°	14'	4.27	24'10"	7.57	46'	14	on request
Optional Extras										
Fitted with a 45° Cone										on request
Fitted with a blower tube and vent										on request



Delivery Costs (Prices available on request)	
Delivery with an escort provided by the client	charged per km
Escort vehicle if required (each way)	charged per km
Minimum delivery fee applies	

Suggested Preparation and Concrete Foundations

The foundation specifications given below are a suggestion only and by no means endorsed by Barunah Pty Ltd. Consultation should be made with a competent authority, with regard to local conditions. Measurements given rely on a measured concrete strength of 25MPa. There should be no gaps between silo base ring and foundation, if so shimming is required under each leg. It is the purchasers responsibility to secure the silo to the foundation.

Foundation						
Models	Silo Diameter M	Approx. Tonnes	Dimension M²	Thickness mm	Concrete M³	Mesh F72
1700/2100/2400	4.27	47-65	4.72	150	3.34	2 Layers



Web: www.barunah.com.au

TASMANIA

Barunah Pty Ltd

Malcolm and Kerry Lee
181 Emu Plains Road (PO Box 124)
WESTBURY TASMANIA 7303

Telephone: 03 6393 1242

Facsimile: 03 6393 2047

Malcolm: 0409938294

Email: barunah06@bigpond.com

